

Switch ON the Innovation
Rackmount / Rack Tower
ON LINE UPS

OL - RM Series

24/7 Full Protection
Designed for IT equipment
Built-in backfeed protection
High-end professional model
Low TCO, High power density
Unmatched Business Continuity



Solution for

- Servers and Networking devices
- Professional and IT equipment
- Data Centers, VoIP and Telecom
- Control System

Ease of Operation

- Rack or Tower configuration
- Extended backup provision
- User Friendly Graphical Interface
- 24/7 availability

Peace of Mind

- Low TCO, High performance
- Wide Input range
- Multiple AH battery adaptability
- Smart monitoring over network

Arrow™ Rackmount/Tower Online UPS Specification

RATING / CAPACITY	KVA	1 KVA to 20 KVA
	Model	Arrow OLRM
INPUT	Voltage Range	160 to 280 Vac Single phase
	Frequency Range	50+/- 5Hz
	Phase	Single Phase
	Generator Input	Support
	Power Factor	≥ 0.98
OUTPUT	Voltage	230V ± 1%
	Frequency (Batt Mode)	50 Hz ± 0.5 Hz
	Crest Factor	3:1
	Harmonic Distortion	± 3% THD (Linear Load)
	Output Waveform	Pure Sinewave
	Efficiency	Better than 90 %
TRANSFER TIME	AC to DC	Zero
	Inverter to Bypass	4/5 ms
INDICATOR	LED / LCD Display	Display of various condition of load, Battery, Input Voltage etc.
	Audible Alarms	On Battery, Low Battery, Over Load, Fault
PROTECTION		Short Circuit, Output Overload, Battery Low, Over Charge
ENVIRONMENT	Operating Temperature	0-40 °C
	Relative Humidity	0 to 95 % Non Condensing
	Noise Level	45 to 55 db
COMMUNICATION (optional)	RS 232 / USB	Interface for Power Management
	External Slot	SNMP / As400 Relay Card / RS 485



True online Rackmount UPS with Double Conversion Topology



Other Product line: Line Interactive & Home UPS Systems, Stabilizers and entire range of Solar Products